

22 - 23 September 2011
Aula Conference Center
TU Delft, The Netherlands

Energetical, Technical and Economical considerations by choosing between a Steam and an Organic Rankine Cycle for Small Scale Power Generation

Delft, September 23th, 2011

Ignace Vankeirsbilck, Bruno Vanslambrouck*, Sergei Gusev

Howest, University College of West Flanders, Kortrijk-Belgium

Department of Masters in Industrial Sciences

Michel De Paepe, Ghent University, Belgium

Department of Flow, Heat and Combustion Mechanics

* Presenting author

22 - 23 September 2011
Aula Conference Center
TU Delft, The Netherlands

1. ORC research objectives
2. The Steam Cycle
3. The Organic Rankine Cycle
4. Benchmark ORC vs Steam
5. Optimal use of a heat source
6. Calculation tool
7. Conclusions

22 - 23 September 2011
Aula Conference Center
TU Delft, The Netherlands


1. ORC research objectives
2. The Steam Cycle
3. The Organic Rankine Cycle
4. Benchmark ORC vs Steam
5. Optimal use of a heat source
6. Calculation tool
7. Conclusions

- To give an answer how to choose between a steam cycle and ORC for a given (waste) heat source related to small scale power generation
- Influence of all process parameters
- Effectiveness of a recuperator
- Influence of temperature profile heat source
- Economic analysis and comparison (not in this presentation)
- Selection criteria steam vs. ORC
- Elaborate industrial case studies
- Demonstrate ORC via a lab scale test rig

1. ORC research objectives
2. The Steam Cycle
3. The Organic Rankine Cycle
4. Benchmark ORC vs Steam
5. Optimal use of a heat source
6. Calculation tool
7. Conclusions


Wide range of steam turbines to recover waste heat and transform into electricity :

- impuls -, reaction turbine
- condensing -, backpressure turbine
- saturated -, superheated steam




Example: Siemens SST series

Live steam pressure : 3 – 130 bara
 Live steam temperature : dry sat. – 530°C
 Exhaust steam pressure : 0,08 – 29 bara
 Speed : 500 – 23000 rpm
 Power : 300 – 10000 kW




- Superheating required to avoid condensation during expansion in turbine
- Only small part of total heat required on high t° level to superheat: no optimal use of the heat source, lower cycle efficiency



Disadvantages to the use of steam on low grade waste heat sources :

- Limited quantity of heat on high level restricts the evaporation pressure and superheating temperature and thus results in low cycle efficiencies.
- Low isentropic efficiency for single stage impuls steam turbine (60 – 65%)

Simulation Simple Steam Cycle



Simulation made in Cycle Tempo (TU Delft)


22 - 23 September 2011
Aula Conference Center
TU Delft, The Netherlands

1. ORC research objectives
2. The Steam Cycle
3. The Organic Rankine Cycle
4. Benchmark ORC vs Steam
5. Optimal use of a heat source
6. Calculation tool
7. Conclusions

- ORC uses similar technology as steam cycle : evaporator - expander – condenser
- But organic work fluid is being used instead of water/steam
- Advantages : smaller quantity of evaporation heat and no superheating needed

Commonly used ORC work fluids :

- Toluene
- (Cyclo)-pentane
- Ammonia
- Butane
- Refrigerants (R245fa)
- Solkatherm
- Siloxanes (silicone oils)




Properties ORC media vs. Steam


		T_{crit}	p_{crit}	Boiling Point	E_{evap} (1bar)
Fluid	Formula / name	[°C]	[bar]	[°C]	[kJ/kg]
Water	H ₂ O	373.9	220.6	100.0	2257.5
Toluene	C ₇ H ₈	318.7	41.1	110.7	365.0
R245fa	C ₃ H ₃ F ₅	154.1	36.4	14.8	195.6
n-pentane	C ₅ H ₁₂	196.6	33.7	36.2	361.8
cyclopentane	C ₅ H ₁₀	238.6	45.1	49.4	391.7
Solkatherm	solkatherm	177.6	28.5	35.5	138.1
OMTS	MDM	291.0	14.2	152.7	153.0
HMDS	MM	245.5	19.5	100.4	195.8

- Water : wet fluid < > ORC media : dry fluids (positive slope saturated vapour)
- Dry fluids : no superheater required
- Application area in function of T_{crit} and p_{crit}
- High BP -> high specific volume at low T condensation
- Low evaporation heat -> high mass flow -> bigger feed pump

StanMix, water




StanMix, Hexamethyldisiloxane



- In simple ORC without regenerator : high quantity of sensible heat after expanders to reject, has negative effect on cycle efficiency.
- Dedicated design of ORC turbines have isentropic efficiency >85%

Simulation ORC


Toluene without regenerator




Simulation made in Cycle Tempo (TU Delft)

ORC with toluene

StanMix, toluene




ORC with regenerator: Sensible heat after expander is used to preheat ORC liquid fluid in regenerator



Simulation made in Cycle Tempo (TU Delft)

Influence of regenerator on net generator efficiency for Toluene with $\eta_{\text{turbine}} = 75\%$



22 - 23 September 2011
Aula Conference Center
TU Delft, The Netherlands

1. ORC research objectives
2. The Steam Cycle
3. The Organic Rankine Cycle
- 4. Benchmark ORC vs Steam**
5. Optimal use of a heat source
6. Calculation tool
7. Conclusions

Comparison application area ORC fluids and water/steam

Simulation assumptions in stationary conditions :

Table 2 : ORC and steam cycle data

Cycle data		
Isentropic efficiency turbine	[%]	75
Pump efficiency	[%]	80
T_{cond}	[°C]	40
q steam outlet turbine	[%]	90
Inlet turbine ORC		Saturated
Inlet turbine steam		Superheated
T_{in} turbine	[°C]	60-500

- no pressure drops or energy losses taken into account
- compare theoretical gross cycle efficiency P_{mech} at turbine shaft
- efficiency gear box, generator not taken into account

Assumptions and remarks:


Comparison application area ORC fluids and water/steam

- Compare gross cycle efficiency of ORC with regenerator vs. simplified steam cycle (results presented on next graph)
- same T inlet turbine for steam cycle as for ORC cycle
- No restrictions on temperature level and thermal power of the heat source

Remarks :

- in reality cycle efficiency will be lower due to pressure drops and energy losses
- Isentropic efficiency depends on used expander type, all simulations are made for η isentropic of 75%
 - Dedicated designed ORC turbines : η isentropic >85%
 - Impuls turbine saturated steam : η isentropic <60%

Gross cycle efficiency ORC with regenerator vs simplified steam cycle



Conclusions ORC fluids:

- ORC fluids : higher efficiency achievable than simplified steam cycle (considering the assumptions and restrictions made)
- Temperature range ORC fluids limited $< 300^{\circ}\text{C}$ (without superheating)
- Efficiency ORC at 300°C comparable to simplified Steam cycle at 400°C , so ORC can be applied on waste heat sources at lower temperatures
- Heat source with $T > 400^{\circ}\text{C}$: steam cycle has higher performance
- Highest cycle efficiency achievable using ORC with toluene (theoretically)

22 - 23 September 2011
Aula Conference Center
TU Delft, The Netherlands

1. ORC research objectives
2. The Steam Cycle
3. The Organic Rankine Cycle
4. Benchmark ORC vs Steam
- 5. Optimal use of a heat source**
6. Calculation tool
7. Conclusions


Influence temperature profile of a (waste) heat source



Temperature profile represents the thermal power available according to the temperature level

Calculation tool: optimal ORC and steam cycle

- Optimal power generated by generator
- Optimal evaporation pressure
- Influence considered parameters on efficiency
 - T_{in} heat source
 - T_{out} heat source
 - P_{th} heat source
 - ORC medium
 - T condensor
 - T evaporator
 - ΔT superheating
 - η_i turbine, pump
 - $\eta_{m,e}$ pump, generator
 - Steam quality
 - With / without regenerator

ORC: Organic Fluid vs Water





RELATIVE HEAT POWER

Comparison of temperature profiles and pinch points for a gas turbine exhaust and water (left) versus R114 (right) as working fluids

Simulation data for example temperature profile :

Table 3 : Data case study temperature profile heat source

Parameter data			
Waste Heat source :		Components	
T profile	350 – 120 °C	η_i pump	80%
P_{th}	3000 kW _{th}	$\eta_{m,e}$ pump	90%
Pinch	20°C	$\eta_{m,e}$ generator	90%
ORC-cycle		Simplified steam cycle	
medium	HMDS	T_{cond}	40°C
ΔT_{sup}	10°C	η_i turbine	70 – 80%
T_{cond}	40°C	q	93%
η_i turbine	70 – 80%	ΔT_{sup}	=f(p_{evap} , T_{cond} , q, η_i turbine)




Table 4 : Results case study temperature profile heat source

		ORC with regenerator			
P_{evap}	[bar]	17.6		14	
η_i turbine	[%]	70	80	70	80
T_{sup}	[°C]	248	248	234	234
$P_{\text{th, reco}}$	[kW _{th}]	2388	2452	2479	2540
$P_{\text{gen, bto}}$	[kW _e]	509	578	506	574
$\eta_{\text{cycle, bto}}$	[%]	21.3	23.6	20.4	22.6
$P_{\text{gen, nto}}$	[kW _e]	487	556	488	556
$\eta_{\text{cycle, nto}}$	[%]	20.4	22.7	19.7	21.9
Case		1	2	3	4

Table summarizes results for ORC with HMDS for different parameters

Realistic expected ORC power (η_i turbine = 80%) : **>500 kW_e**

(Example : Turboden HR 6 : 2850 kW_{th} – 545 kW_e)

Table 4 : Results case study temperature profile heat source

		Simplified steam cycle					
P_{evap}	[bar]	6		12		18	
η_i turbine	[%]	70	80	70	80	70	74
T_{sup}	[°C]	219	267	272	330	305	329
$P_{\text{th, reco}}$	[kW _{th}]	2737	2715	2386	2357	2134	2121
$P_{\text{gen, bto}}$	[kW _e]	440	509	442	509	426	450
$\eta_{\text{cycle, bto}}$	[%]	16.1	18.7	18.5	21.6	19.9	21.2
$P_{\text{gen, nto}}$	[kW _e]	439	508	441	508	424	449
$\eta_{\text{cycle, nto}}$	[%]	16.0	18.7	18.5	21.5	19.9	21.2
Case		5	6	7	8	9	10

Table summarizes results for steam cycle with different parameters

Realistic expected power simplified steam cycle : **~440 kW_e** (~ -10 à -15% ORC)

(η_i turbine = 70%)

Some conclusions for case study on temperature profile heat source :

- ORC can be operated even a with low evaporation pressure on low grade heat sources, and still achieve an acceptable cycle efficiency compared to a (simplified) steam cycle
- ORC's require higher mass flows, and therefore bigger feed pumps which have a negative impact on net electric power
- The heating curves of ORC's can be better matched to the temperature profile of a low grade heat source, resulting in a higher cycle efficiency and in a higher recovery ratio for the thermal power.

22 - 23 September 2011
Aula Conference Center
TU Delft, The Netherlands

1. ORC research objectives
2. The Steam Cycle
3. The Organic Rankine Cycle
4. Benchmark ORC vs Steam
5. Optimal use of a heat source
- 6. Calculation tool**
7. Conclusions


Tools :

- Calculation tool for cycle efficiency and generated power for ORC
- Calculation tool for cycle efficiency and generated power for steam cycle
- Calculation tool for optimal net generated power for any given temperature profile of a waste heat source



Tools output :

- Charts with influence of all parameters on cycle efficiency and generated power
- Optimal heating profile for ORC and steam cycle matching any heat source (optimal T evaporator, p evaporator, T superheating)
- Automatic generation of QT-diagram
- Automatic representation of ORC and steam cycle on Ts-diagram



- Influence charts for all parameters on cycle efficiency and generated power



- Optimal heating profile for ORC and steam cycle matching any heat source (optimal T evaporator, p evaporator, T superheating)
- Automatic generation of QT-diagram



- Automatic presentation of ORC and steam cycle on Ts-diagram



22 - 23 September 2011
Aula Conference Center
TU Delft, The Netherlands

1. ORC research objectives
2. The Steam Cycle
3. The Organic Rankine Cycle
4. Benchmark ORC vs Steam
5. Optimal use of a heat source
5. Calculation tool
6. Conclusions

ORC

Pro:

- low t° heat sources usable
- lower pressure in the system
- less complex installation
- no superheater needed
- easy to operate (“one button” start)
- small scale (from 0,3 kWe) available
- better part load efficiency

Contra:

- often thermal oil intermediate
- working fluid probably toxic, flammable



Steam cycle

Pro:

- “standard” technology
- more flexibility in power/heat ratio
- water/steam as working fluid
- direct evaporation in HR exchanger

Contra:

- needs higher t° sources (from ca 150°C)
- more complex installation (water treatment, deaerator...)
- higher system pressure
- only “higher” power range (from ca 300 kWe)

Thanks to all of you for your attention

Time for questions...discussion ?



ing. Bruno Vanslambrouck

HOWEST, division of Electromechanics
Research Group on Thermodynamics
Graaf Karel de Goedelaan 5, B-8500 Kortrijk

Mail: bruno.vanslambrouck@howest.be

Tel: +32 56 241211 of +32 56 241227 (dir)

www.howest.be

www.orcycle.eu