

Making shipping greener: ORC modelling in challenging environments

Santiago Suarez de la Fuente, Alistair R. Greig

University College London

08/10/2013

Contents of presentation

- Motivation
- The Ship → Waste Heat Recovery
- Objectives and Methodology
- Results
- Conclusions
- Future Work

Motivation

- Shipping CO₂ emissions / Energy Efficiency Design Index (EEDI).
- Lack of comparison between thermodynamic waste heat recovery systems (WHRS) under shipping scenarios.
- How ship's operational conditions affect the performance of the thermodynamic WHRS?




(1)

Propulsive Energy Map

Hull Friction
Wave Generation




Other losses
 $\approx 15\%$



(3)



$\approx 50\%$



(4)



Low/Medium waste heat

(Between
30 – 650°C)


- Exhaust gas
- Scavenge air
- Cooling Water
- Other



(5)




Only a maximum of
35% of the
combustion energy
ends as propulsion
power (2)



- Power Increase
- Fuel Consumption reduction
- CO_2 reduction

Ship's WHRS characteristics



Objectives

**Water
Rankine Cycle**

VS

**Organic
Rankine Cycle**



Compare under ship's operating conditions:

- Thermal Efficiency
- Power Output
 - Fuel Consumption
 - CO₂ Emission reduction

(8)

Ship's WHRS

	Rankine Cycle	Organic Rankine Cycle
Manufacturers	MAN and Wärtsilä	OPCON
Used in	Exhaust Gas System	Boiler System
Comments	<ul style="list-style-type: none"> Assisted with a gas turbine to cover larger scope of engine loadings Benefits of up to 12% of the power output. (9) 	<ul style="list-style-type: none"> Limited to steam not used (Low quality heat). Achieves a 5% fuel consumption reduction. (10)

Few papers talk about them in a ship scenario, but they have not been yet compared under variable conditions.

	Rankine Cycle	Organic Rankine Cycle
Authors	(Hatchman 1991) (11), (Theotokatos & Livanos 2012) (12)	(Ghirardo et al. 2011) (13), (Larsen et al. 2013) (14)

- To find the WHRS optimum points the high pressure was changed up to the Critical pressure.


Assumptions

- The exhaust gas is treated as air, with its heat capacity as the average temperature between the exhaust inlet and outlet.
- The electrical efficiency of the generator and pumps are the same and stay constant.
- No pressure changes except for the expander and pump.
- No heat losses in the working fluid circuit except the ones set for the heat exchangers.
- No leakages.
- Steady-state operation.
- The equipment is capable of handling different mass flow rates and pressures.

The Engine

MAN slow speed Diesel Model 14K98ME7.1-TII with four turbos (15).

- Engine's Fuel Consumption per hour @85% MCR:
12.70 Metric tons of Marine Diesel Oil
- Power output @85% MCR: 74,137 kW
- Steam production @85% MCR: 15,240 kg/h



T - Turbos

The Engine

The performances are at the maximum net power output obtained in each engine loading scenario. Some points are shown in the following table (15).

Engine Load (% MCR)	Power (kW)	Exhaust mass flow rate (kg/h)	Specific Fuel Oil Consumption (g/kWh)	Temperature (K)	Specific heat (kJ/kg-K)
100	87,200	744,300	175.5	557.15	1.028
85	74,137	687,300	171.3	518.15	1.025
75	65,415	647,700	168.6	491.15	1.022
50	43,610	465,300	169.5	501.15	1.023
40	34,888	385,200	171.7	516.15	1.025
30	26,166	352,200	174.1	482.15	1.022
25	21,805	297,500	176.1	488.15	1.022
15	13,083	212,000	184.1	468.15	1.020


Generator

- In order to understand the magnitude of the fuel savings it was used for this comparison a Wärtsilä 16V32 genset with the following characteristics:
 - Electrical Power: 8430 kW_e (with an efficiency of around 96%)
 - Fuel consumption: 176 g/kWh.
 - Fuel used: Marine Diesel Oil.
 - Cost per metric ton: €697 (26/09/2013) (17)



(16)

WHRS Layout



Working Fluids

Working Fluids	T_c^* (K)	P_c^* (MPa)	Notes from the fluid ⁺
Water	647.10	22.06	
Benzene	562.02	4.91	Highly flammable, irritating.
Toluene	591.75	4.13	Extremely flammable, irritating.
Heptane	540.13	2.74	Highly flammable, irritating, harmful to aquatic life.
Hexamethyldisiloxane (MM)	518.70	1.94	Highly flammable, irritating, harmful to aquatic life.

These fluids were selected because of their Low Global warming and Ozone depleting coefficient.

* (18)

+ Comments are written as found in the Annex VI Regulation 1272/2008 of the Institute for Health for Consumer Protection (19).

Results: Variable Engine Loading

Maximum electric power output

- Highly dependant in the heat availability.


Higher

Benzene
5.7 MWe

Lower

Water
4.8 MWe

18.4% lower





Results: Variable Engine Loading

Thermal efficiency

- Highly dependant in the heat quality.


Higher

MM
24.5%

16.3% higher

Lower

Water
20.5%



Results: Variable Engine Loading

Fuel savings (assuming mechanical power)

- Highly dependant in the heat quality.


Higher
Benzene

€732/h

An overall improvement of
15.6% from RC

Lower
Water

€618/h



Operational hours

- A container ship works around 6,480 hours per year.
- The engine loading in a year is as follows (9):

Engine Load (% MCR)	Percentage of time (%)	Total hours in a year (h)
100	1	65
90	5	324
85	5	324
80	20	1296
75	15	972
70	15	972
60	10	648
50	10	648
35	13	842
15	6	389

} **Design point**

Points not appearing in the table had insignificant operating time.



Results: Variable Engine Loading

Fuel savings in a year


Higher

Benzene
€1.71
million

In 20 year of operations the ORC will save around **€4 million** more than RC

Lower

Water
€1.51
million




Results: Variable Engine Loading CO₂ reductions in a year

Higher
Benzene
7,880 CO₂
Tons

In 20 year of operations the ORC will save around **18x10³ CO₂ tons** more than RC

Lower
Water
6,940 CO₂
Tons



The different WHRS are sensible to the heat quality and availability, but also their benefit is affected by the engine's own performance.

ORC WHRS outperforms the RC by:


- Improving the shipping CO₂ emissions reductions.
- Increasing the vessel efficiency (fuel and energy savings).
- Reduces operational costs.

But is still important to:

- Assess the effects of mass flow rate and pinch point temperature in the WHRS size.
- Find working fluids with lower levels of flammability and toxicity.

Future work

- Improve model by adding expander and pump models.
- Equipment sizing so it will be possible to address how the mass flow rate and pinch point temperature affects the WHRS.
- Find organic fluids that can reduce hazards.



(21)

Thank you

Questions ?



Works Cited

1. Blake Q. The Green Ship [Internet]. Quentin Blake. 2013. p. 1. Available from: <http://thebuddingbookworm.blogspot.co.uk/2010/07/green-ship.html>
2. Organization IM. International maritime organization. 2009 p. 289.
3. World Shipping Council. Container Vessel Fleet. 2013 [cited 2013 Jun 05] <http://www.worldshipping.org/about-the-industry/liner-ships/container-vessel-fleet>
4. Gcaptian. Shipping [Internet]. 2011 [cited 2013 Jun 05] <http://gcaptain.com/tag/ship-engines/>
5. Plumbr. Thinking. Shipping [Internet]. 2012 [cited 2013 Jun 05] <http://plumbr.eu/blog/whats-your-overhead/thinking>
6. Sailors Club. Marine Engineering Technology for More Efficient Shipping [Internet]. 2012 [cited 2013 Jun 05]. p. 1. Available from: http://www.sailors-club.net/index.php?option=com_myblog&show=2012-07-18-10-35-00.html&Itemid=101
7. 123RF - Illustration - environment protection concept [Internet]. Available from: http://www.123rf.com/photo_12831315_environment-protection-concept--save-nature--paper-ship-with-green-leaves-blossom-tree-branch.html
8. Sail Training International. Tall Ships Race Events [Internet]. 2013 [cited 2013 Jun 05]. p. 1. Available from: www.sailtraininginternational.org
9. MAN Diesel & Turbo. Waste Heat Recovery System (WHRS) for Reduction of Fuel Consumption, Emission and EEDI. Copenhagen; 2012 p. 32.

Works Cited

10. Opcon Energy Systems AB. Commissioning and testing of first reference installation of Opcon technology for ships. Stockholm: Opcon Energy Systems AB; 2012. p. 2.
11. 123RF - Illustration - environment protection concept [Internet]. Available from: http://www.123rf.com/photo_12831315_environment-protection-concept--save-nature--paper-ship-with-green-leaves-blossom-tree-branch.html
12. Hatchman JC. Steam cycles for waste heat recovery: A case study. R&D Journal. 1991;7(3):32–8.
13. Theotokatos G, Livanos G. Techno-economical analysis of single pressure exhaust gas waste heat recovery systems in marine propulsion plants. Proceedings of the Institution of Mechanical Engineers, Part M: Journal of Engineering for the Maritime Environment. 2012 Oct 15;227(2):83–97.
14. Ghirardo F, Santin M, Traverso A, Massardo A. Heat recovery options for onboard fuel cell systems. International Journal of Hydrogen Energy. Elsevier Ltd; 2011 Jul;36(13):8134–42.
15. MAN Diesel & Turbo. Engine room and performance data for 14K98ME7.1-TII with 4 x MAN TCA88-21 and part load exhaust gas bypass (EGB) tuning. MAN Diesel & Turbo; 2013. p. 10.
16. Wärtsilä 16V32 [Internet]. Available from: <http://www.wartsila.com/en/engines/gensets/generating-sets>
17. Bunker Index MDO [Internet]. Available from: http://www.bunkerindex.com/prices/bixfree.php?priceindex_id=4#Description

Works Cited

18. Lemmon EW., Huber ML., McLinden MO. NIST Reference Fluid Thermodynamic and Transport Properties Database. Gaithersburg: National Institute of Standards and Technology; 2010.
19. Institute for Health for Consumer Protection. Annex VI to Regulation (EC) No 1272/2008 on Classification, Labelling and Packaging of Dangerous Substances. Annex VI to Regulation (EC) No 1272/2008. 2008. p. 1.
20. Rightship. Calculating and Comparing CO2 Emissions from the Global Maritime Fleet. London; 2011 p. 24.
21. HHP Insight. Container Ship LNG? Plenty of Time. [Internet]. Available from: <http://hhpinsight.com/marine/2013/01/container-ship-lng-plenty-of-time/>

Results: Constant Engine Loading

Thermal efficiency at 75% MCR


Higher

Heptane
21.9%

2.3% higher and
88.1% more net
power than RC

Lower

Water
21.4%



Results: Constant Engine Loading

Net Power Output at 75% MCR


Higher

Benzene
2,222 kW

11.8% larger

Lower

Water
1,987 kW



Results: Constant Engine Loading

Mass flow rate at 75% MCR


Higher

MM
34.8 kg/s

More than
700% larger

Lower

Water
4.8 kg/s



Results: Variable Engine Loading

WHRS Electrical Power returned

- Highly dependant in the heat quality.

Higher
Benzene

68.0%

A maximum difference of
15.7% from RC

Lower
Water

57.3%

