

Conference Presentation

AMSE-ORC 2013

Rotterdam – October 8th 2013



Non-constant wall thickness scroll expander investigation for a micro solar ORC power plant

by

Ir. Rémi DICKES (MIT/ULg)
Dr. Matt OROSZ (MIT)
Pr. Harry HEMOND (MIT)

PRESENTATION STRUCTURE

1

- 1) Context and Issues
- 2) Optimal scroll geometries selection
- 3) CAD modeling of a single stage prototype
- 4) Prototype fabrication and assembly
- 5) Conclusion and perspectives

PART 1

2

CONTEXT AND ISSUES

1. Context and Issues

3

Environmental
concerns

Electricity access
in developing
countries

Favorable insolation
conditions

MicroCSP




Photovoltaic



MicroCSP = Micro “Concentrated Solar Power” plant |||| ORC = Organic Rankine Cycle

1. Context and Issues


3



1. Context and Issues

4

MicroCSP description:





- 1) Sun rays
- 2) Parabolic trough collectors
- 3) ORC unit
- 4) Off-grid electric load
- 5) Ambient air
- 6) Thermal storage

1. Context and Issues

4

MicroCSP description:



Operating conditions (T_{ev}/T_{cond})

Low Carnot efficiency



Improve expansion device

MicroCSP = micro 'Solar Power Power' plant

1. Context and Issues

4

MicroCSP description:



MicroCSP = micro 'Solar Power Power' plant

1. Context and Issues

5

Motivations for a new design of scroll expander

- Optimized internal volumetric ratios
- Two-stage/single-shaft architecture
 - Single signal frequency f and output voltage V
 - Half of the power electronic required → cheaper and more simple
- Variable wall thickness profile
 - More compact expansion device
 - Heat and mechanical losses reduced

1. Context and Issues

5

Motivations for a new design of scroll expander:

- Optimized internal volumetric ratios
- Two-stage/single-shaft architecture
 - Single signal frequency f and output voltage V
 - Half of the power electronic required → cheaper and more simple
- Variable wall thickness profile
 - More compact expansion device
 - Heat and mechanical losses reduced

1. Context and Issues

5

Motivations for a new design of scroll expander:

- Optimized internal volumetric ratios
- Two-stage/single-shaft architecture
 - Single signal frequency f and output voltage V
 - Half of the power electronic required → cheaper and more simple
- Variable wall thickness profile
 - More compact expansion device
 - Heat and mechanical losses reduced

$$CF = \frac{r_v}{D} \rightarrow \text{prop. to } \eta_{is}$$

PART 2

6

OPTIMAL SCROLL GEOMETRIES SELECTION

2. Optimal scroll geometries selection

7

- Operating requirements given by a steady-state model (EES)

○ $135^{\circ}\text{C} \rightarrow 35^{\circ}\text{C}$

○ 5kW

○ R245fa

○ 3000 rpm


○ $\dot{W}_{1st} = \dot{W}_{2nd}$

$$r_{v,1st} = 4.9$$

$$r_{v,2nd} = 3.36$$

$$\dot{m} = 0.15 \text{ kg/s}$$

$$V_{in}$$



2. Optimal scroll geometries selection



8

- Minimum wall thickness requirement



Cantilever beam theory :

$$e_{min} = \sqrt[3]{\frac{3 \cdot \Delta P \cdot h^5}{2 E \delta_{max}}}$$



2. Optimal scroll geometries selection

9



Danfoss frame



1 geometry ⇔ 8 parameters

$$s_x = c_1 + c_2 \varphi + c_3 \varphi^2 + c_4 \varphi^3 + c_5 \varphi^4$$

R, d and N

2. Optimal scroll geometries selection

10


26.000 scrolls
database

r_v criteria
CF ranking

26 candidates

Deterministic
modeling

2 geometries
selected




$$CF = \frac{r_v}{D}$$

↓

prop. to η_{is}

2. Optimal scroll geometries selection

10



2. Optimal scroll geometries selection


11



Deterministic model of a scroll expander taking into account

- ✦ Radial and flank leakages
- ✦ Intake and exhaust throttling losses
- ✦ Friction losses between the scrolls
- ✦ Mechanical losses into the bearings

η_{is} , \dot{W} , FF



2. Optimal scroll geometries selection

12





1st stage:

- $\eta_{1st,is} = 73.12\%$
- highest CF among candidates
- $\dot{W} = 3.03 \text{ kW}$

2nd stage:

- $\eta_{2nd,is} = 66.14 \%$
- highest CF among candidates
- $\dot{W} = 2.5 \text{ kW}$



Full expansion: $\eta_{is,tot} = 68.6 \%$

2. Optimal scroll geometries selection

12




1st stage:

- $\eta_{1st,is} = 73.12\%$
- highest CF among candidates
- $\dot{W} = 3.03 \text{ kW}$

2nd stage:

- $\eta_{2nd,is} = 66.14 \%$
- highest CF among candidates
- $\dot{W} = 2.5 \text{ kW}$

Full expansion: $\eta_{is,tot} = 68.6 \%$



2. Optimal scroll geometries selection

13

- Losses study

Losses modeled	First stage		Second stage	
----	η (%)	$\Delta\eta$ (%)	η (%)	$\Delta\eta$ (%)
Inlet/Outlet Throttling losses	97.19	-	88.7	-
<i>Same as the previous</i> + Mechanical losses	82.77	14.43	68.75	19.95
<i>Same as the previous</i> + Flank leakages	77.26	5.51	68.02	0.73
<i>Same as the previous</i> + Radial leakages	73.67	3.59	66.68	1.34
<i>Same as the previous</i> + Heat losses	73.12	0.55	66.14	0.54

2. Optimal scroll geometries selection

13

- Losses study

Losses modeled	First stage		Second stage	
----	η (%)	$\Delta\eta$ (%)	η (%)	$\Delta\eta$ (%)
Inlet/Outlet Throttling losses	97.19	-	88.7	-
<i>Same as the previous</i> + Mechanical losses	82.77	14.43	68.75	19.95
<i>Same as the previous</i> + Flank leakages	77.26	5.51	68.02	0.73
<i>Same as the previous</i> + Radial leakages	73.67	3.59	66.68	1.34
<i>Same as the previous</i> + Heat losses	73.12	0.55	66.14	0.54





Main source : mechanical losses

2. Optimal scroll geometries selection

14

- Losses study : mechanical source analysis




Losses source	First stage	Second stage
Thrust bearing	42.1 W	74.06 W
Journal bearing (top)	269.8 W	276.3 W
Journal bearing (low)	179.9 W	184.2 W
Scroll friction	33.07 W	181.6 W
TOTAL	≈530 W	≈ 720 W

2. Optimal scroll geometries selection

15

Performance enhancement?

Design	A	B	C
<i>Wall thickness profile</i>	Constant	Constant	Decreasing
<i>Volumetric ratio</i>	2,8 (both stages)	Optimized	Optimized
\dot{W}_{tot}	5.04 kW	5.45 kW	5.5 kW
$\eta_{is,tot}$	62.4 %	67.43 %	68.6 %





2. Optimal scroll geometries selection

15

Performance enhancement?

Design	A	B	C
Wall thickness profile	Constant	Constant	Decreasing
Volumetric ratio	2,8 (both stages)	Optimized	Optimized
\dot{W}_{tot}	5.04 kW	5.45 kW	5.5 kW
$\eta_{is,tot}$	62.4 %	67.43 %	68.6 %


$$\Delta \eta_{is,tot} = 5.03\%$$


$$\Delta \eta_{is,tot} = 1.17\%$$



$$\Delta \eta_{is,tot} = +6.2\%$$


2. Optimal scroll geometries selection

15

Performance enhancement?

Design	A	B	C
<i>Wall thickness profile</i>	Constant	Constant	Decreasing
<i>Volumetric ratio</i>	2,8 (both stages)	Optimized	Optimized
\dot{W}_{tot}	5.04 kW	5.45 kW	5.5 kW
$\eta_{is,tot}$	62.4 %	67.43 %	68.6 %


$$\Delta \eta_{is,tot} = 5.03\%$$


$$\Delta \eta_{is,tot} = 1.17\%$$



$$\Delta \eta_{is,tot} = +6.2\%$$

2. Optimal scroll geometries selection

15

Performance enhancement?

Design	A	B	C
<i>Wall thickness profile</i>	Constant	Constant	Decreasing
<i>Volumetric ratio</i>	2,8 (both stages)	Optimized	Optimized
\dot{W}_{tot}	5.04 kW	5.45 kW	5.5 kW
$\eta_{is,tot}$	62.4 %	67.43 %	68.6 %



PART 3

16

CAD MODELING OF A SINGLE-STAGE PROTOTYPE

3. CAD modeling of a single-stage prototype

17

- CAD modeling
- SolidWorks 2012
- Architecture derived from Copeland compressors (ZR series)
- Expander: 30 assembled pieces



3. CAD modeling of a single-stage prototype

18


- Mechanical viability checked by a 60% scale 3D-printed model (FDM printer)
- Oil delivery circuit/BPC control system
- CAM with HSMXpress



3. CAD modeling of a single-stage prototype

18


- Mechanical viability checked by a 60% scale 3D-printed model (FDM printer)
- Oil delivery circuit and BPC control system
- CAM with HSMXpress



3. CAD modeling of a single-stage prototype

18

- Mechanical viability checked by a 60% scale 3D-printed model (FDM printer)
- Oil delivery circuit and BPC control system
- CAM with HSMXpress



PART 4

19

PROTOTYPE FABRICATION AND ASSEMBLY

20



4. Prototype fabrication and assembly

21



4. Prototype fabrication and assembly

22



PART 5

23

CONCLUSION AND PERSPECTIVES

5. Conclusion & Perspectives

24

- Finish the single-stage prototype
 - Check the envelope sealing
 - Instrumentation
 - Oil delivery circuit & BPC circuit piping
- Experimental test and validation
 - Test rig at Eckerd College (FL)
 - Validate the deterministic model
 - (Update the second stage geometry)
- Design and fabrication of the two-stage prototype

5. Conclusion & Perspectives

24

- Finish the single-stage prototype
 - Check the envelope sealing
 - Instrumentation
 - Oil delivery circuit & BPC circuit piping
- Experimental test and validation
 - Test rig at Eckerd College (FL)
 - Validate the deterministic model
 - (Update the second stage geometry)
- Design and fabrication of the two-stage prototype

Test rig (Eckerd College – FL)

25

Collectors

Condenser

ORC unit


HTF tank



5. Conclusion & Perspectives

26

- Finish the single-stage prototype
 - Check the envelope sealing
 - Instrumentation
 - Oil delivery circuit & BPC circuit piping
- Experimental test and validation
 - Test rig at Eckerd College (FL)
 - Validate the deterministic model
 - (Update the second stage geometry)
- Design and fabrication of the two-stage prototype



Thank you for your attention

27

QUESTIONS ?

More information : *Design and fabrication of a variable wall thickness two-stage scroll expander to be integrated in micro-solar power plant* - Master thesis – Rémi DICKES

APPENDIX



Variable wall thickness geometries → Danfoss frame

1 geometry \Leftrightarrow 8 parameters

$$S_x = c_1 + c_2 \varphi + c_3 \varphi^2 + c_4 \varphi^3 + c_5 \varphi^4$$

R, d and N



Warning : non reversible process! → random generation

Select the best candidates among a database


All parameter combinations are not viable

- Only exploring viable parameter domains
- Using a hierarchical parameter selection strategy

APPENDIX



APPENDIX



APPENDIX

